



Simply irresistible. Superior light quality from start to finish

MasterColor CDM-R Elite

The Elite family is at the very top of the MasterColor CDM range, and gives a unique combination of unbeatable light quality and consistent performance over lifetime, while keeping running costs low. MasterColor metal halide lamps deliver consistent white light and higher color rendering than any standard metal halide source for architectural lighting. MasterColor CDM Elite PAR30L lamps deliver similar performance as the MasterColor Elite family lamps in the familiar PAR30L shape.

Benefits

- Energy-efficient alternative to incandescent, halogen and standard MasterColor PAR30L lamps.
- Improved lumen maintenance over standard metal halide and standard MasterColor PAR30L lamps.
- Lamp to lamp color consistency over life.

Features

- Exceptional color rendering and superior color stability -- within +/- 200 K, CRI 90, 3000 K
- Low mercury, no lead; ALTO-compliant
- Operates on existing electronic and electromagnetic ballasts
- Features FadeBlock™—an integrated UV-blocking medium for reduced fading of fabrics and paintings
- Available in 35 and 70 W versions

Application

- Ideal for display and accent lighting in retail and architectural lighting for interior and exterior applications.

MasterColor CDM-R Elite

Warnings and Safety

- R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)
- Lamp contains mercury.
- Manage in Accord with Disposal Laws.
- See: www.lamprecycle.org or 1-800-555-0050

Versions




35 W Single Contact Medium
Screw PAR 2.5 inch Clear CCT of
3000K

Dimensional drawing

D

Product	D (max)	C (max)
MASTERColor CDM-R Elite 35W/930 E26 PAR20 30D	2-9/16 in	3-3/4 in



Product	D (max)	C (max)
MASTERColor CDM-R Elite 35W/930 E26 PAR30L 30D	3-13/16 in	4-7/8 in
MASTERColor CDM-R Elite 70W/930 E26 PAR30L 40D	3-13/16 in	4-7/8 in

MasterColor CDM-R Elite

Controls and dimming

Dimmable	No
----------	----

Operating and electrical

Re-Ignition Time (Min) (Max)	15 min
Warm Up Time To 60% Light (Nom)	120 s

General information

Cap-Base	E26
Life To 10% Failures (Nom)	10000 h
Life To 20% Failures (Nom)	12000 h
Life To 50% Failures (Nom)	15000 h
Life To 5% Failures (Nom)	9000 h
Operating Position	Universal
Switching Cycle	1350X

Luminaire design requirements

Bulb Temperature (Max)	572 °F
------------------------	--------

Light technical

Beam Description	Flood
Color Code	930
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	3000 K
Llmf At End Of Nominal Lifetime (Nom)	80 %
Lumen Maintenance 12000 h (Nom)	82 %
Lumen Maintenance 2000 h (Nom)	94 %
Lumen Maintenance 4000 h (Nom)	90 %

Mechanical and housing

Bulb Finish	Clear
-------------	-------

Approval and application

Order Code	Full Product Name	Energy Consumption kWh/1000 h	Mercury (Hg) Content (Nom)
434191	MASTERColor CDM-R Elite 35W/930 E26/24 PAR20 30D	43 kWh	4.7 mg
426486	MASTERColor CDM-R Elite 35W/930 E26/24 PAR30L 30D	43 kWh	4.7 mg
426544	MASTERColor CDM-R Elite 70W/930 E26/24 PAR30L 40D	80 kWh	6.6 mg

Operating and electrical

Order Code	Full Product Name	Voltage (Max)	Voltage (Min)	Voltage (Nom)	Power (Nom)
434191	MASTERColor CDM-R Elite 35W/930 E26/24 PAR20 30D	96 V	80 V	88 V	39 W
426486	MASTERColor CDM-R Elite 35W/930 E26/24 PAR30L 30D	96 V	80 V	88 V	39 W

Order Code	Full Product Name	Voltage (Max)	Voltage (Min)	Voltage (Nom)	Power (Nom)
426544	MASTERColor CDM-R Elite 70W/930 E26/24 PAR30L 40D	93 V	79 V	86 V	73.0 W

Light technical (1/2)

Order Code	Full Product Name	Beam Angle (Nom)	Chromaticity Coordinate X (Nom)	Chromaticity Coordinate Y (Nom)	Color Rendering Index (Min)
434191	MASTERColor CDM-R Elite 35W/930 E26/24 PAR20 30D	30 °	0.437	0.400	88

Order Code	Full Product Name	Beam Angle (Nom)	Chromaticity Coordinate X (Nom)	Chromaticity Coordinate Y (Nom)	Color Rendering Index (Min)
426486	MASTERColor CDM-R Elite 35W/930 E26/24 PAR30L 30D	30 °	0.437	0.400	88

MasterColor CDM-R Elite

Order Code	Full Product Name	Beam Angle (Nom)	Chromaticity Coordinate X (Nom)	Chromaticity Coordinate Y (Nom)	Color Rendering Index (Min)
426544	MASTERColor CDM-R Elite 70W/930 E26/24 PAR30L 40D	40 °	0.443	0.402	89

Light technical (2/2)

Order Code	Full Product Name	Color Rendering Index (Nom)	Luminous Efficacy (rated) (Nom)	Design Mean Lumens	Luminous Intensity (Nom)
434191	MASTERColor CDM-R Elite 35W/930 E26/24 PAR20 30D	91	61 lm/W	2040 lm	5800 cd
426486	MASTERColor CDM-R Elite 35W/930 E26/24 PAR30L 30D	91	69 lm/W	2300 lm	8000 cd


Order Code	Full Product Name	Color Rendering Index (Nom)	Luminous Efficacy (rated) (Nom)	Design Mean Lumens	Luminous Intensity (Nom)
426544	MASTERColor CDM-R Elite 70W/930 E26/24 PAR30L 40D	92	70 lm/W	4510 lm	9300 cd

Mechanical and housing


Order Code	Full Product Name	Bulb Shape
434191	MASTERColor CDM-R Elite 35W/930 E26/24 PAR20 30D	PAR20
426486	MASTERColor CDM-R Elite 35W/930 E26/24 PAR30L 30D	PAR30L

Order Code	Full Product Name	Bulb Shape
426544	MASTERColor CDM-R Elite 70W/930 E26/24 PAR30L 40D	PAR30L




Color Rendering Diagrams



LDCR_CDM-R-E_35W_930_PAR30L-Colour rendering diagram





LDCR_CDM-R-E_70W_930_PAR30L-Colour rendering diagram





MasterColor CDM-R Elite

Accent Diagrams



Beam Diagrams



LDAC_CDM-R-E_0016-Beam diagram

LDAC_CDM-R-E_0001-Beam diagram

LDAC_CDM-R-E_0005-Beam diagram

