



MSR Gold™ MiniFastFit – lamp replacement in seconds

MSR Gold™ MiniFastFit (Touring/Stage)

Thanks to the specially designed lamp base, the MSR Gold™ MiniFastFit takes just seconds to replace, to help ensure non-stop clubbing entertainment. In addition, the innovative gold plated pins ensure excellent current transfer to prolong lamp and lamp holder lifetimes and thereby reduce lamp replacement costs. Easy handling and small compact fixture designs are allowed by the lamps compact size, while the very short arc provides a high perceived brightness and high beam intensity.

Benefits

- Lamp replacement in just seconds
- Easy handling, smaller and lighter fixtures
- Reduces early lamp or lamp holder failures. Excellent current transfer
- High perceived brightness
- High beam intensity

Features

- Philips MiniFastFit
- Compact design
- Innovative gold plated pins
- High color temperature
- Very short arc

MSR Gold™ MiniFastFit (Touring/Stage)

Application

- Events
- Shows
- Touring/Stage

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Lamp contains mercury. Manage in Accord with Disposal Laws. See: www.lamprecycle.org or 1-800-555-0050

Versions

MSR Gold™ 1000 MiniFastFit



MSR Gold™ 300/2 MiniFastFit




MSR Gold™ 400, 575/2, 700(1,2)
MiniFastFit




MSR Gold™ MiniFastFit (Touring/Stage)

Dimensional drawing



| Product | D (max) | O | L (min) | L (max) | L | C (max) | F (max) | F | F (min) |
|--------------------|---------|--------|---------|---------|-------|---------|---------|-------|---------|
| MSR Gold™ 400 | 23.2 mm | 3.0 mm | 55 mm | 57 mm | 56 mm | 111 mm | 36.5 mm | 36 mm | 35.3 mm |
| MiniFastFit 1CT/16 | | | | | | | | | |
| MSR Gold™ 575/2 | 23.2 mm | 3.5 mm | 55 mm | 57 mm | 56 mm | 112 mm | 36.5 mm | 36 mm | 35.3 mm |
| MiniFastFit 1CT/4 | | | | | | | | | |
| MSR Gold™ 700 | 23 mm | 3.5 mm | 55 mm | 57 mm | 56 mm | 116 mm | 36.5 mm | 36 mm | 35.3 mm |
| MiniFastFit 1CT/16 | | | | | | | | | |
| MSR Gold™ 700/1 | 23.2 mm | 3.8 mm | 55 mm | 57 mm | 56 mm | 112 mm | 36.5 mm | 36 mm | 35.3 mm |
| MiniFastFit 1CT/4 | | | | | | | | | |
| MSR Gold™ 700/2 | 23.2 mm | 3.8 mm | 55 mm | 57 mm | 56 mm | 112 mm | 36.5 mm | 36 mm | 35.3 mm |
| MiniFastFit 1CT/4 | | | | | | | | | |

| Product | D (max) | O | L (min) | L (max) | L | C (max) |
|-------------------|---------|--------|---------|---------|---------|---------|
| MSR Gold™ 300/2 | 23 mm | 5.0 mm | 65.8 mm | 67.8 mm | 66.8 mm | 126 mm |
| MiniFastFit 1CT/4 | | | | | | |



| Product | D (max) | O | L (min) | L (max) | L | C (max) | F (max) | F | F (min) |
|-------------------|---------|--------|---------|---------|-------|---------|---------|-------|---------|
| MSR Gold™ 1000 | 26 mm | 5.5 mm | 55 mm | 57 mm | 56 mm | 112 mm | 36.5 mm | 36 mm | 35.3 mm |
| MiniFastFit 1CT/4 | | | | | | | | | |

MSR Gold™ MiniFastFit (Touring/Stage)

Controls and Dimming

| | |
|----------|-----|
| Dimmable | Yes |
|----------|-----|

General Information

| | |
|--------------------|---------------|
| Main Application | Entertainment |
| Operating Position | Universal |
| System Description | MiniFastFit |

Operating and Electrical

| Order Code | Full Product Name | Lamp Current (Nom) | Power (Rated) (Nom) |
|------------|-----------------------------------|--------------------|---------------------|
| 260471 | MSR Gold™ 1000 MiniFastFit 1CT/4 | 11.4 A | 1000.0 W |
| 287177 | MSR Gold™ 300/2 MiniFastFit 1CT/4 | 3.75 A | 300 W |
| 287201 | MSR Gold™ 575/2 MiniFastFit 1CT/4 | 10.2 A | 575 W |
| 248963 | MSR Gold™ 400 MiniFastFit 1CT/16 | 7.2 A | 400 W |

| Order Code | Full Product Name | Lamp Current (Nom) | Power (Rated) (Nom) |
|------------|-----------------------------------|--------------------|---------------------|
| 277095 | MSR Gold™ 700 MiniFastFit 1CT/16 | 10.8 A | 700 W |
| 292565 | MSR Gold™ 700/1 MiniFastFit 1CT/4 | 10.2 A | 700 W |
| 286922 | MSR Gold™ 700/2 MiniFastFit 1CT/4 | 10.2 A | 700 W |

General Information


| Order Code | Full Product Name | Cap-Base (Nom) | Life To 50% Failures (Nom) |
|------------|-----------------------------------|----------------|----------------------------|
| 260471 | MSR Gold™ 1000 MiniFastFit 1CT/4 | PGJX36 | 900 h |
| 287177 | MSR Gold™ 300/2 MiniFastFit 1CT/4 | PGJX28 | 750 h |
| 287201 | MSR Gold™ 575/2 MiniFastFit 1CT/4 | PGJX28 | 750 h |
| 248963 | MSR Gold™ 400 MiniFastFit 1CT/16 | PGJX28 | 750 h |

| Order Code | Full Product Name | Cap-Base (Nom) | Life To 50% Failures (Nom) |
|------------|-----------------------------------|----------------|----------------------------|
| 277095 | MSR Gold™ 700 MiniFastFit 1CT/16 | PGJX28 | 750 h |
| 292565 | MSR Gold™ 700/1 MiniFastFit 1CT/4 | PGJX28 | 750 h |
| 286922 | MSR Gold™ 700/2 MiniFastFit 1CT/4 | PGJX28 | 750 h |

Light Technical

| Order Code | Full Product Name | Color Code | Correlated Color Temperature (Nom) | Color Rendering Index (Nom) | Luminous Flux (Min) | Luminous Flux (Nom) |
|------------|-----------------------------------|------------|------------------------------------|-----------------------------|---------------------|---------------------|
| 260471 | MSR Gold™ 1000 MiniFastFit 1CT/4 | - | 6000 K | 80 | 74000 lm | 82000 lm |
| 287177 | MSR Gold™ 300/2 MiniFastFit 1CT/4 | 2 | 9300 K | 80 | 19170 lm | 21300 lm |
| 287201 | MSR Gold™ 575/2 MiniFastFit 1CT/4 | 2 | 7500 K | 70 | 34500 lm | 38600 lm |
| 248963 | MSR Gold™ 400 MiniFastFit 1CT/16 | - | 6700 K | 60 | 23400 lm | 26000 lm |
| 277095 | MSR Gold™ 700 MiniFastFit 1CT/16 | - | 6000 K | 65 | 44500 lm | 49000 lm |
| 292565 | MSR Gold™ 700/1 MiniFastFit 1CT/4 | 1 | 5700 K | 73 | - | 53400 lm |
| 286922 | MSR Gold™ 700/2 MiniFastFit 1CT/4 | 2 | 7200 K | 75 | 44000 lm | 47000 lm |

Color Rendering Diagrams



XDCR_XDMSR_400W-Colour Rendering Vector diagram

MSR Gold™ MiniFastFit (Touring/Stage)

