



Energy saving elegance in a familiar design

LED A15

Philips A15 LED Lamps offer energy saving ambience with an elegant effect. Their unique design provides light in all directions, giving lighting designers a long life alternative to standard incandescent sources.

Benefits

- Long life -- lowers maintenance costs by reducing re-lamp frequency
- Excellent color consistency with high color rendering (CRI)
- Certain offerings with a warm glow effect dim to a cozy glow to set the mood

Features

- Integrated compact driver design to achieve a decorative look and feel
- Smooth dimming
- Installs into existing candelabra and medium-base fixtures
- 15,000-hour rated average life
- Wet location

Application

- Chandeliers
- Marque lighting
- Fans

LED A15

Versions



Candelabra Screw



Single Contact Medium Screw





Single Contact Medium Screw A
15mm Clear



Single Contact Medium Screw A
15mm Transparent Amber

Dimensional drawing



Product	D	C
5A15/PER/950/CL/G/E26/DIM 1FB T20	47 mm	86 mm
3.8A15/PER/927-922/CL/G/E26/WGX1FB T20	47 mm	86 mm
5.5A15/PER/927-922/CL/G/E26/WGX1FB	47 mm	86 mm
3.3A15/VIN/820/E26/CL/GL/DIM 4/FBHT20	47 mm	84 mm

Product	D	C
3.8A15/PER/927-922/CL/G/E12/WGX1FB T20	47 mm	92 mm
5.5A15/PER/927-922/CL/G/E12/WGX1FB	47 mm	92 mm

LED A15

Approval and Application	
Energy Consumption kWh/1000 h	- kWh
Controls and Dimming	
Dimmable	Yes
Operating and Electrical	
Voltage (Nom)	120 V
Starting Time (Nom)	0.5 s
General Information	
Nominal Lifetime (Nom)	15000 h
Switching Cycle	20000X
Mechanical and Housing	
Bulb Shape	A15

Operating and Electrical

Order Code	Full Product Name	Input Frequency	Wattage Equivalent	Power (Rated) (Nom)
549378	3.8A15/PER/927-922/CL/G/E12/WGX1FB T20	50 to 60 Hz	40 W	3.8 W
549394	5.5A15/PER/927-922/CL/G/E12/WGX1FB	50 to 60 Hz	60 W	5.5 W
549386	3.8A15/PER/927-922/CL/G/E26/WGX1FB T20	50 to 60 Hz	40 W	3.8 W

Order Code	Full Product Name	Input Frequency	Wattage Equivalent	Power (Rated) (Nom)
549402	5.5A15/PER/927-922/CL/G/E26/WGX1FB	50 to 60 Hz	60 W	5.5 W
548305	5A15/PER/950/CL/G/E26/DIM 1FB T20	60 Hz	40 W	5 W
556555	3.3A15/VIN/820/E26/CL/GL/DIM 4/FBHT20	60 Hz	25 W	3.3 W

General Information

Order Code	Full Product Name	Cap-Base
549378	3.8A15/PER/927-922/CL/G/E12/WGX1FB T20	E12
549394	5.5A15/PER/927-922/CL/G/E12/WGX1FB	E12
549386	3.8A15/PER/927-922/CL/G/E26/WGX1FB T20	E26

Order Code	Full Product Name	Cap-Base
549402	5.5A15/PER/927-922/CL/G/E26/WGX1FB	E26
548305	5A15/PER/950/CL/G/E26/DIM 1FB T20	E26
556555	3.3A15/VIN/820/E26/CL/GL/DIM 4/FBHT20	E26

Light Technical

Order Code	Full Product Name	Color Code	Correlated Color Temperature (Nom)	Color Rendering Index (Nom)	Llmf At End Of Nominal Lifetime (Nom)	Luminous Flux (Nom)
549378	3.8A15/PER/927-922/CL/G/E12/WGX1FB T20	927-922	- K	90	70 %	350 lm
549394	5.5A15/PER/927-922/CL/G/E12/WGX1FB	927-922	- K	90	70 %	500 lm
549386	3.8A15/PER/927-922/CL/G/E26/WGX1FB T20	927-922	- K	90	70 %	350 lm
549402	5.5A15/PER/927-922/CL/G/E26/WGX1FB	927-922	- K	90	70 %	500 lm
548305	5A15/PER/950/CL/G/E26/DIM 1FB T20	950	5000 K	90	0.7 %	450 lm
556555	3.3A15/VIN/820/E26/CL/GL/DIM 4/FBHT20	820	2000 K	80	70 %	200 lm

Mechanical and Housing

LED A15

Order Code	Full Product Name	Bulb Finish
549378	3.8A15/PER/927-922/CL/G/E12/WGX1FB T20	Clear
549394	5.5A15/PER/927-922/CL/G/E12/WGX1FB	Clear
549386	3.8A15/PER/927-922/CL/G/E26/WGX1FB T20	Clear

Order Code	Full Product Name	Bulb Finish
549402	5.5A15/PER/927-922/CL/G/E26/WGX1FB	Clear
548305	5A15/PER/950/CL/G/E26/DIM 1FB T20	Clear
556555	3.3A15/VIN/820/E26/CL/GL/DIM 4/FBHT20	Transparent Amber

Temperature

Order Code	Full Product Name	T-Case Maximum (Nom)
549378	3.8A15/PER/927-922/CL/G/E12/WGX1FB T20	50 °C
549394	5.5A15/PER/927-922/CL/G/E12/WGX1FB	60 °C
549386	3.8A15/PER/927-922/CL/G/E26/WGX1FB T20	50 °C
549402	5.5A15/PER/927-922/CL/G/E26/WGX1FB	60 °C
548305	5A15/PER/950/CL/G/E26/DIM 1FB T20	50 °C
556555	3.3A15/VIN/820/E26/CL/GL/DIM 4/FBHT20	50 °C

