



Reflector Infrared BR40, PAR38

125BR40 IR/1/TG 120V 4/1

Philips Family of Specialty Incandescents provide the perfect light for dramatic accents and display lighting as well as general lighting in a variety of applications. Philips Infrared lamps are suited for heating and drying in industrial and commercial applications. These incandescent, gas-filled infrared heat lamps come up to full temperature almost immediately, eliminating costly warm-up time. Highly efficient heat generators that produce a minimum of light rays and a high amount of infrared radiation. The BR40 lamp provides a built-in reflector for radiant energy control.

Product data


General Information		
Base	E26 [Single Contact Medium Screw]	incapacitated persons may be dangerous.—Lamp should not be placed closer than 18" to the surface being irradiated.
Operating Position	Universal [Universal]	—Do not use for therapeutic or topical applications unless recommended by a physician.—For food warming, use only lamps with heat resisting glass. (89)
Main Application	Infrared	
Gas Filling	GAS	
Footnote Incandescent 1	Average laboratory life in excess of 5000 hours. In-service life depends upon service conditions. (27)	Footnote Incandescent 4
Footnote Incandescent 2	Do not allow hot bulb to come in contact with liquid or metal parts of the fixture, as glass may shatter. Do not use outdoors. Do not operate in close proximity to flammable materials or those adversely affected by heat or drying. Operate only in heat resistant sockets. (87)	Circle E-The encircled E means this bulb meets Federal minimum efficiency standards.
Footnote Incandescent 3	CAUTION: Do not operate in close proximity to flammable materials or those adversely affected by heat or drying. Operate only in heat resistant sockets. WARNING: Use carefully. May cause serious burns. Do not use over insensitive skin areas or in the presence of poor circulation. The unattended use of infrared heat by children or	Rated Lifetime (Hours)
		5000 h
		Light Technical
		Beam Description
		Spot
		Operating and Electrical
		Power (Rated) (Nom)
		125 W
		Voltage (Nom)
		120 V
		Mechanical and Housing
		Bulb Finish
		Clear

Reflector Infrared BR40,PAR38

Cap-Base Information	Aluminium [Aluminium Cap]
Filament Shape	C-9 [Pendant]
Bulb Shape	BR40 [BR40 (BR40)]
Product Data	
Order product name	125BR40 IR/1/TG 120V 4/1
EAN/UPC - Product	046677159306
Order code	159301

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	925254936309
Net Weight (Piece)	0.001 kg

Dimensional drawing



125W E26 120V BR40 SP CL

Product

125BR40 IR/1/TG 120V 4/1

