



Actinic BL TL-D(K) Secura

ACTINIC BL15W/10 SECURA 25PK

With an optimized spectrum matching the eye sensitivity of the housefly, Actinic BL TL-D(K) Secura lamps are perfect for attracting insects. They have virtually no UV-B output, and so are perfectly safe. In addition, they have a special "Secura" sleeve that keeps all glass and components together in the case of accidental breakage. This eliminates the risk of glass splinters showering down on food preparation areas, for example. And that is why it meets the strict HACCP requirements. What's more, with the lowest mercury content in the industry and being 100% lead-free, these lamps represent a very good environmental choice.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Lamp contains mercury.
- Manage in Accord with Disposal Laws.
- See: www.lamprecycle.org or 1-800-555-0050

Product data

General Information		Operating and Electrical	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]	Power Consumption	15 W
Light Technical		Lamp Current (Nom)	0.335 A
Color Code	10	Voltage (Nom)	55 V
Color Designation	Actinic	Voltage (Nom)	55 V
Chromaticity Coordinate X (Nom)	222	Mechanical and Housing	
Chromaticity Coordinate Y (Nom)	210	Bulb Shape	T26 [T 26mm]

Actinic BL TL-D(K) Secura

Approval and Application


Mercury (Hg) Content (Nom) 5.5 mg

Product Data

Full product code 871150089858640
Order product name Actinic BL TL-D 15W/10 Secura 1SL/25
Order code 215186


Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material number (12NC)	928024701029
Full product name	ACTINIC BL15W/10 SECURA 25PK
EAN/UPC - Case	8711500898593

Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
Actinic BL TL-D 15W/10 Secura 1SL/25	28 mm	437.4 mm	444.5 mm	442.1 mm	451.6 mm

Photometric data



Spectral Power Distribution Colour - Actinic BL TL-D 15W/10 Secura 1SL/25

