

LED G25

2.7G25/PER/927-922/CL/G/E26/WGX1FB T20

Philips G25 LED Lamps offer energy saving ambience with an elegant effect. Their unique design provides light in all directions, giving lighting designers a long life alternative to standard incandescent sources.

Product data

General Information	
Base	E26 [Single Contact Medium Screw]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	15000 h
Switching Cycle	20000X
Technical Type	2.7-25W

Light Technical	
Color Code	927-922 [CCT of 2700K-2200K]
Initial lumen (Nom)	250 lm
Color Designation	Warm Glow(WG)
Correlated Color Temperature (Nom)	- K
Luminous Efficacy (rated) (Nom)	92.00 lm/W
Color Consistency	<4
Color Rendering Index (Nom)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Input Frequency	50 to 60 Hz
Power (Rated) (Nom)	2.7 W
Lamp Current (Nom)	30 mA
Wattage Equivalent	25 W
Starting Time (Nom)	0.5 s
Warm Up Time to 60% Light (Nom)	0.5 s

Power Factor (Nom)	0.75
Voltage (Nom)	120 V

Temperature	
T-Case Maximum (Nom)	45 °C

Controls and Dimming	
Dimmable	Yes


Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	G25 (G25)

Approval and Application	
Energy Consumption kWh/1000 h	- kWh

Product Data	
Order product name	2.7G25/PER/927-922/CL/G/E26/WGX1FB T20
EAN/UPC - Product	046677549350
Order code	549352
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929002204704
Net Weight (Piece)	0.040 kg

LED G25



Dimensional drawing



CandIG25120V2.7-25W250lm2700-2200KE26DCL

Product	D	C
2.7G25/PER/927-922/CL/G/E26/WGX1FB T20	80 mm	121 mm


Photometric data



OSRAM Reference ID: 400119101 Page 1/1

LEDbulb CL,FR 927


LEDbulb 25W E26 G25 927 CL



LEDbulb 927 CL

LED G25

Lifetime



15K LED

15K LMP

