



MASTER LEDtube InstantFit HF T5

Master LEDtube HF 1500mm HE 20W 865 T5

The Philips MASTER LEDtube integrates a LED light source into a traditional fluorescent form factor. Its unique design creates a perfectly uniform visual appearance, which cannot be distinguished from traditional fluorescent. These T5 lighting tubes are the right choice for absolute performance and are designed to stand up to everyday conditions. Unparalleled savings thanks to low energy consumption and an exceptionally long lifetime make these T5 LED tubes the choice for every demanding application.

Product data


General information		Operating and electrical	
Base	G5 [G5]	Input Frequency	30K to 100K Hz
EU RoHS compliant	Yes	Power (Rated) (Nom)	20 W
Nominal Lifetime (Nom)	60000 h	Lamp Current (Max)	350 mA
Switching Cycle	50000X	Lamp Current (Min)	150 mA
Flux measurement reference	Sphere	Starting Time (Nom)	0.5 s
		Warm Up Time to 60% Light (Nom)	0.5 s
		Power Factor (Nom)	0.92
		Voltage (Nom)	80-130 V
Light technical		Temperature	
Color Code	865 [CCT of 6500K]	T-Ambient (Max)	113 °F
Beam Angle (Nom)	200 °	T-Ambient (Min)	-4 °F
Initial lumen (Nom)	3000 lm	T-Storage (Max)	149 °F
Color Designation	Cool Daylight	T-Storage (Min)	-40 °F
Correlated Color Temperature (Nom)	6500 K	T-Case Maximum (Nom)	149 °F
Luminous Efficacy (rated) (Nom)	150 lm/W		
Color Consistency	<6		
Color Rendering Index (Nom)	80		
LLMF At End Of Nominal Lifetime (Nom)	70 %		

MASTER LEDtube InstantFit HF T5

Controls and dimming	
Dimmable	Yes - Check ballast compatibility
Mechanical and housing	
Bulb Finish	Frosted
Bulb Material	Glass
Product Length	60 in
Bulb Shape	Tube, double-ended
Approval and application	
Energy Efficiency Class	D
Energy Saving Product	Yes
Approbation Marks	TUV
Approbation Marks	RoHS compliance CE marking KEMA Keur certificate

Energy Consumption kWh/1000 h	20 kWh
EPREL Registration Number	406191
Product data	
Order product name	Master LEDtube HF 1500mm HE 20W 865 T5
EAN/UPC - Product	8718696743393
Order code	366401
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001391502
Copy Net Weight (Piece)	0.432 lb


Dimensional drawing



Master LEDtube HF 1500mm HE 20W 865 T5


Product	D1	D2	A1	A2	A3
Master LEDtube HF 1500mm HE 20W 865 T5	5/8 in	3/4 in	57-1/16 in	57-3/8 in	57-5/8 in

Photometric data



General Uniform Lighting
 T500 20W T5 x Tube 20W 865 3000lm
 L x 1500mm
 © 2022 Philips Lighting B.V.
 Product Reference: 41
 Photo Lighting 8.1
 Page 11


LEDtube 1500mm 20W G5 865 3000lm



LEDtube 1500mm 20W G5 865 3000lm


MASTER LEDtube InstantFit HF T5

Photometric data




LEDtube 600mm 8W G5 830 1000lm


Lifetime




LifetimeVsTc



FailureRate




Lumen Maintenance Diagram



Life Expectancy Diagram

MASTER LEDtube InstantFit HF T5

Lifetime



LEDtube MAS SLR 20W 60K LumenVsTc-LMP

