



# LED PAR30 S/L

## 8.5PAR30L/LED/930/F25/DIM/GULW/T20 6/1FB

Philips LED spots with a single optic beam, provide a clean beam that's free from shadows with beam angles from 15 and 40 degrees to suit every general lighting application.

### Product data

General information	
Base	E26 [ Single Contact Medium Screw]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	25000 h
Switching Cycle	25000
Light technical	
Color Code	930 [ CCT of 3000K]
Beam Angle (Nom)	25 °
Initial lumen (Nom)	850 lm
Luminous Intensity (Nom)	3300 cd
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	100.00 lm/W
Color Consistency	<4
Color Rendering Index (Nom)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and electrical	
Input Frequency	50 to 60 Hz
Power (Rated) (Nom)	8.5 W
Lamp Current (Nom)	80 mA
Wattage Equivalent	75 W
Starting Time (Nom)	0.5 s


Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.9
Voltage (Nom)	120 V
Temperature	
T-Case Maximum (Nom)	158 °F
Controls and dimming	
Dimmable	Only with specific dimmers
Mechanical and housing	
Bulb Finish	Clear
Bulb Material	Glass
Bulb Shape	PAR30L [ PAR 3.75 inch/95mm Long]
Approval and application	
Suitable For Accent Lighting	Yes
Energy Certifications	Energy Star
Product data	
Order product name	8.5PAR30L/LED/930/F25/DIM/GULW/T20 6/1FB
EAN/UPC - Product	046677567958
Order code	567957

# LED PAR30 S/L

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	929003027004

Net Weight (Piece)	0.628 lb
--------------------	----------



## Dimensional drawing



8.5PAR30L/LED/930/F25/DIM/GULW/T20 6/1FB


Product	D	C
8.5PAR30L/LED/930/F25/DIM/GULW/T20 6/1FB	3-3/4 in	4-9/16 in

## Photometric data



LEDspots N DIM 8,5W PAR30L E26 930 25D-LDD

LEDspots N DIM 8,5W PAR30L E26 930 25D 1-ADL



LEDspots N DIM 8,5W PAR30L E26 930 25D-POC

# LED PAR30 S/L

## Lifetime



Life Expectancy Diagram

Lumen Maintenance Diagram

