



Halogen reflector

ELC 13163 24V 250W

Philips' halogen reflector lamps offer the ideal no-fuss solution for a wide variety of medical, projection and scientific illumination systems. Their proven reliability makes them ideal for retrofit installations. The burners are precisely aligned for optimal light performance. Dichroic reflectors ensure heat dissipation towards the back of the optical system, which helps the optical system remain within temperature limits. A special blue-filter version blocking out unwanted light above 700 nm is available for dental curing applications. In addition, you get all the proven advantages of halogen technology such as a CRI of 100 – the same as natural sunlight for the best possible color rendering. Halogen lamps also create a comfortable warm white light, and they maintain their high lumen output with almost no lumen reduction throughout their lifetime.

Product data


General Information		Controls and Dimming	
Base	GX5.3 [GX5.3]	Dimmable	Yes
Philips Code	13163	Mechanical and Housing	
ANSI Code	ELC	Bulb Material	Quartz-UV Open
LIF Code	A1/259	Reflector Finish	Smooth
Operating Position	Universal [Universal]	Filament Dimensions WxH	-
Main Application	Projection	Luminaire Design Requirements	
Life to 50% Failures (Nom)	50 h	Bulb Temperature (Max)	900 °C
Light Technical		Pinch Temperature (Max)	400 °C
Color Rendering Index (Nom)	100	Working Distance WD	35 mm
Operating and Electrical		Product Data	
Power (Rated) (Nom)	250 W	Order product name	13163 250W GX5.3 24V 1CT/10X5F
Voltage (Nom)	24 V	EAN/UPC - Product	8711500409751

Halogen reflector

Order code	507095
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	923919720501

Net Weight (Piece)	0.024 kg
--------------------	----------

Dimensional drawing



13163 250W GX5.3 24V

Product	D (max)	C (max)
13163 250W GX5.3 24V 1CT/10X5F	50 mm	44.5 mm

