



MSR Gold™ MiniFastFit (Touring/ Stage)

MSR Gold™ 400 MiniFastFit 1CT/16

Thanks to the specially designed lamp base, the MSR Gold™ MiniFastFit takes just seconds to replace, to help ensure non-stop clubbing entertainment. In addition, the innovative gold plated pins ensure excellent current transfer to prolong lamp and lamp holder lifetimes and thereby reduce lamp replacement costs. Easy handling and small compact fixture designs are allowed by the lamps compact size, while the very short arc provides a high perceived brightness and high beam intensity.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Lamp contains mercury. Manage in Accord with Disposal Laws. See: www.lamprecycle.org or 1-800-555-0050

Product data


General Information		Initial lumen (Nom)	
Base	PGJX28 [PGJX28]	Initial lumen (Nom)	26000 lm
Operating Position	Universal [Universal]	Chromaticity Coordinate X (Nom)	310
Main Application	Entertainment	Chromaticity Coordinate Y (Nom)	320
Life to 50% Failures (Nom)	750 h	Correlated Color Temperature (Nom)	6700 K
System Description	MiniFastFit	Luminous Efficacy (rated) (Nom)	65 lm/W
		Color Rendering Index (Nom)	60
Light Technical		Operating and Electrical	
Color Code	- [Not Specified]	Power (Rated) (Nom)	400 W
Initial lumen (Min)	23400 lm	Lamp Current (Nom)	7.2 A

MSR Gold™ MiniFastFit (Touring/Stage)

Ignition Supply Voltage (Min)	198 V
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Cap-Base Information	PGJX28
Luminaire Design Requirements	
Bulb Temperature (Max)	950 °C
Pinch Temperature (Max)	500 °C

Product Data	
Order product name	MSR Gold™ 400 MiniFastFit 1CT/16
EAN/UPC - Product	8718291158288
Order code	248963
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	16
Material Nr. (12NC)	928194005114
Net Weight (Piece)	0.053 kg

Dimensional drawing



MSR GOLD 400 MiniFastFit

Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSR Gold™ 400 MiniFastFit 1CT/16	23.2 mm	3.0 mm	55 mm	57 mm	56 mm	111 mm	36.5 mm	36 mm	35.3 mm

